

538,331

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/067389 A2

- (51) International Patent Classification⁷: B65D
- (21) International Application Number:
PCT/NO2003/000409
- (22) International Filing Date: 9 December 2003 (09.12.2003)
- (25) Filing Language: Norwegian
- (26) Publication Language: English
- (30) Priority Data:
20025958 11 December 2002 (11.12.2002) NO

CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (71) Applicant and
(72) Inventor: NÆSJE, Kjetil [NO/NO]; Askeveien 8, N-4314 SANDNES (NO).

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- (74) Agent: HÅMSØ PATENTBYRÅ ANS; P.O. Box 171, N-4302 SANDNES (NO).


Published:

— without international search report and to be republished upon receipt of that report

- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A VALVE DEVICE HAVING TWO MEMBRANES FOR A DRINKING CONTAINER



(57) Abstract: An underpressure-activated valve device for a drinking container (32). The device consists of an outer membrane (2) and an inner membrane (4) that are placed at an axial distance from one another, and their peripheral attachment areas are pressure-sealingly interconnected, causing a reference pressure chamber (6) having at least one vent (8) to an ambient pressure P1 to exist between the membranes (2, 4). One membrane (2, 4) is fixedly connected to a flow pipe (10), and the other membrane (4, 2) is provided with a membrane opening (12) within which the pipe (10) is movably arranged. The membrane opening (12) is associated with a primary sealing body (18) for sealing against fluid flow via the pipe (10), and with a secondary sealing body (16) for sealing contact with the pipe (10) when the valve device is in an inactive position of rest, while at least the primary sealing body (18) is placed in an open position when the valve device is in an active position.

WO 2004/067389 A2